266 Wayfarer® 14 mm unbacked







- Standard size CiTi™ mat, 14 mm unbacked, for lose lay, with pressed beveled borders on all four sides.
- Vinyl loops scrape dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building (does not absorb water).
- Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface.
- This unbacked version allows water to flow through.
- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Suitable for heavy traffic conditions.
- For placement interior facility entrances or recessed wells.
- Vacuum clean or wash off with hose.
- Free of toxic DOP and DMF.

266 Wayfarer® 14 mm unbacked

PRODUCT SPECIFICATIONS		
Designation		Dust Control Matting
Description		Thick coils of « Spaghetti » matting
Type		Non-absorbent / scrape vinyl mat
Material		
	Top	Thick coils (strand diameter 1 mm) of extruded from 100% PVC
	Backing	Unbacked
Process		Extrusion
Category		Outdoor Non absorbent - Spaghetti
Recommended use		Outdoor - heavy foot traffic
Colours		Grey, Red, Navy Blue
Weight		4,6 kg/m²
Thickness		14 mm
Standard sizes		90 cm x 150 cm 120 cm x 180 cm
Custom sizes		
Special remarks		UV resistant

PRODUCT TESTING		
Tests	**Norms**	**Results**
Abrasion resistance	ASTM D3884	4.7% weight loss
Colour fastness to light	AATCC 16E	
Accelerated wear test by sim floor machine	U.S.	5
Accelerated soiling	U.S.	4
Anti-slip	DIN51130 BGR181	R11
Water retention	U.S	
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044983.07.

FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	Bfl - S1
Sustainability		• Recyclable material • REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals	

NOTRAX® FLOOR MATTING

www.notrax.eu