Mat Seaming Tape





- Black vinyl seaming tape with patterned gluing surface for a secure bond.
- Embossed protective paper ensures gluing surface remains clean.
- Apply Notrax® Glue to patterned side of seaming tape.
- It is recommended to seam mats from the same roll in the same direction of the carpet grain for an undetectable seam.

Recommended uses:

· For width wise or lengthwise seaming of vinyl backed carpet matting.

Full rolls:

- 5 cm x 45.7 m
- 8 cm x 45.7 m

Custom lengths:

- 5 cm x per linear meter
- 8 cm x per linear meter
- 5 cm x per linear meter mounted
- 8 cm x per linear meter mounted

Sizes	Weight kg
5 cm x 45,7 m	2.1
5 cm per linear meter	0.05
5 cm per linear meter, mounted	0.05
8 cm x 45,7 m	3.8
8 cm per linear meter	0.08
8 cm per linear meter, mounted	0.08
	5 cm x 45.7 m 5 cm per linear meter 5 cm per linear meter, mounted 8 cm x 45.7 m 8 cm per linear meter



092 Mat Seaming Tape

GENERAL DESCRIPTION

Designation	Dust Control Matting				
Туре	Accessories - Dust Contr	Accessories - Dust Control Matting			
Description	Black vinyl seaming tap	Black vinyl seaming tape for joining mats.			
Surface Pattern	Embossed patterned sur	face			
Category	Mat Accessories				
Recommended Use	Indoor/Outdoor				
Colours	Black				
Dimensions	Standard Sizes	Full Rolls	Custom Lengths		
	N/A	5 cm x 45.7 m	5 cm x linm		
		8 cm x 45.7 m	8 cm x linm		
Special Remarks	Recommended to seam undetectable seam.	Recommended to seam mats from the same batch in the direction of the carpet grain for an undetectable seam.			
Accessories	Notrax® Glue				

TECHNICAL SPECIFICATIONS

Material	Vinyl
Backing	Release paper
Process	Extrusion
Weight	0,01 kg/m²
PVC Thickness	4.7
Foam Thickness	9.3 mm
Overall Thickness	2 mm

TESTS

Compression Deflection	1.4 kg/cm ²		
·	2.8 kg/cm ² :		
Foam Battery	ASTM D3574		
Abrasion Resistance	ASTM D3884-01 500 cycles		
Static Coefficient of Friction	ASTM D412 1000 cycles		
Elongation	ASTM D412		
Breaking Load	ASTM D412		
Graves Tear Strength	ASTM D1004		
Hardness	ASTM D2240-02		
Anti-Slip	DIN 51130		
Fire Rating	EN 13501-1		
ESD	ISO 105 E02 Rp:		
	Rg:		
Chemical Resistance			
Temperature Range			
Sustainability			
	Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).		

