

430 Skywalker HD Curve™



- 100% natural rubber for general purpose applications
- 45-degree wedge made of high quality rubber for maximum durability and excellent standing comfort.
- The bubble surface provides a sure footing and optimal ergonomic effects in stationary standing positions.
- The unique design and craftsmanship make the mat easy to handle and easy to install. Compatible with the Skywalker HD™ series, this interlocking 45-degreee wedges of 91 cm length can be easily assembled for unique configurations for corners, S-curves, half-moons and complete circles.
- Attachable yellow or black ramps have curved bevelled edges to prevent tripping on the mat.
- Clean by sweeping or vacuuming.
- Designed to yield a long service life.
- Resistant to most chemicals.
- Free of silicone therefore safe for vehicle painting facilities.





430 Skywalker HD Curve™

	PF	ODUCT SPECIFICATIONS		
Designation	Industrial matting			
Туре	Anti-fatigue			
Description	Modular system			
Material	100% natural rubber compound - Not for use in contact with oils and animal fats.			
Process	Compression moulding			
Category	Best			
Recommended use	Heavy duty – dry industrial environments			
Colours	Black			
Weight	4,3 kg/mat			
Thickness	13 mm			
Standard sizes	91 cm 45-degree curve			
Custom sizes	N/A			
Special remarks		Accessories: Skywalker HD Curve™ Ramp System™ male attachable bevels 91 cm yellow and black.		
		PRODUCT TESTING		
	Tests	Norms	Results	
Compression deflection		U.S.		
		ASTM D575		
		ASTM D575		
Foam battery		ASTM D3574		
Abrasion resistance		ASTM D3884-01		
	1000 Cycles		0.824	
	5000 Cycles			
Static coefficient of friction		ASTM C1028-96		
Elongation		DIN 53455-6-4	210%	
Breaking load		ASTM D412	4.80 Mpa	
Graves tear strength		ASTM D 1004	10.5 N/mm	
Hardness		ASTM D2240-02	67 Shore A	
Anti-slip		DIN 51130 and BG-RULE BGR181	R9	
		FIRE TESTING		
	Critical radiant flux	ASTM E-648		
	Fire retorden av	DIN4102		
	Fire retardancy	EN 13501-1		
	Flammability test	ASTM D2859	5 min.	
ESD		ANSI ESD S7.1 50% Humidity		
Sustainability		 Recyclable material Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 		

